

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G01N 35/00	A2	(11) International Publication Number: WO 00/63704 (43) International Publication Date: 26 October 2000 (26.10.00)
(21) International Application Number: PCT/US00/08930 (22) International Filing Date: 4 April 2000 (04.04.00) (30) Priority Data: 09/293,313 16 April 1999 (16.04.99) US (71) Applicant: PERSEPTIVE BIOSYSTEMS, INC. [US/US]; 500 Old Connecticut Path, Framingham, MA 01701 (US). (72) Inventors: TAYLOR, Todd, A.; 10 Vernon Street, Framingham, MA 01701 (US). CARSON, William, W.; 14 Schofield Road, Hopkinton, MA 01748 (US). KOUTNY, Lance; 45 Washington Street #86, Methuen, MA 01844 (US). (74) Agent: BRODOWSKI, Michael, H.; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).		(81) Designated States: JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: APPARATUS AND METHODS FOR SAMPLE ANALYSIS (57) Abstract The present invention is directed to apparatus and methods for rapid, automated, microscale sample analysis using pressure differentials. The invention includes an apparatus having intersecting channels for introduction of a sample and separation of that sample into its components. The sample introduction and separation channels preferably are etched in a microfabricated device, such as a microchip, to form a junction. Pressure gradients are applied to the channels to form a sample plug in the separation channel. The separation channel may have disposed within it a medium for separation of the components suspected to be contained in the sample. For example, with the proper medium, a voltage gradient may be applied along the separation channel to separate the components of the sample electrophoretically. The apparatus also may include means for detecting the components of the sample subsequent to separation.		

Best Available Copy

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KR	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon		Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Licchtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

APPARATUS AND METHODS FOR SAMPLE ANALYSIS

FIELD OF THE INVENTION

The present invention relates to apparatus and methods for sample analysis. More specifically, the invention is directed to apparatus and methods for sample plug formation and subsequent separation and/or analysis.

BACKGROUND OF THE INVENTION

- 5 Methods for conducting and analyzing microscale chemical reactions often require multiple steps and extensive handling of reagents. These methods typically are labor intensive and involve complex combinations of instrumentation, e.g., pipettes, pumps, syringes, valves, tubing, reagent vessels, and reaction chambers. Such complexities may contribute to inaccuracies, increased costs and reduced reaction yields.
- 10 Analytical techniques typically require a high degree of labor and the use of complex apparatus. Moreover, many laboratory and industrial chemical processes involve the use of relatively large volumes of reagents and multiple laboratory instruments. Typical large scale immunoassays, e.g., require the use of pipettes, reagent vessels, and reaction chambers. *See, e.g.,* Mattiasson *et al.*, *Proc. Int. Symp. on Enzyme-Labeled Immunoassay of Hormones and Drugs*,
15 (Pal, S., Ed., Walter de Gruyter, Berlin (1978), p. 91). Such processes, regardless of the size of the reaction, also may require multiple steps. Accordingly, there is a potential for reduced accuracy due to the introduction of impurities, volumetric inaccuracies, and low reproducibility. These problems especially are acute in microscale diagnostic applications in which biological samples are analyzed, such as, e.g., immunoassays, polynucleotide amplifications, or
20 hybridizations.

- Recently, efforts have been made to streamline chemical processes to reduce costs, increase accuracy, and improve reaction yields. For example, capillary electrophoresis techniques have been proposed to increase resolution in immunoassays. Various attempts have been made to enhance other common analytical techniques, such as the polymerase chain
25 reaction (PCR). For example, U.S. Patent 5,273,907 reports a capillary pre-loaded with PCR

- 2 -

reagents which is used to deliver a sample to the reagents for DNA amplification. Similarly, International Patent Publication WO 93/22058 describes a micro-scale device for performing PCR. In this case, PCR reagents from a first chamber are mixed with sample in a second chamber by movement of materials through channels in a microchip.

5 Recently, efforts have been made to streamline chemical processes to reduce labor and complexity. One such effort involves the use of microchip assemblies. A microchip assembly typically consists of a thin silica substrate or other polymeric substrate onto which channels are etched. The channels serve as means for reagent transport and/or as the reaction chambers themselves. Microchip assemblies for performing micro-scale chemical reactions may comprise
10 a series of interconnected channels. For example, channels may be etched onto the surface of a microfabricated solid. Reagents in solution then are placed into the channels, and allowed to react with, e.g., reagents already in the channels. Voltage gradients may be used to control sample flow and mixing. *See, e.g.*, International Publication WO 96/04547. Hydrogen and oxygen gas often results from use of voltage gradients to control sample flow. Electrolysis
15 products also may accumulate near the electrode surface.

Microchip assemblies which do not require voltage gradients to inject the samples and solutions have been designed. *See, e.g.*, U.S. Patent No. 5,304,487; International Publication WO 93/22053; and International Publication WO 93/22054 (describing microchip assemblies for sample analysis). In such systems, a steady flow of liquid is pumped through a series of channels
20 etched on a microchip. Sample is introduced through one of the channels and is mixed with the flow of liquid. These systems are used to detect the presence of a sample component or the presence of some biological entity (a bacterium or virus, e.g.) by measuring the variance in flow rate between liquid and liquid mixed with sample as each flows through the microchip.

There remains a need in the art for methods and devices which will decrease the time,
25 labor, costs, biohazard exposure and complexity currently involved in the performance of chemical analysis of microscale biological samples. More particularly there exists a need for apparatus and methods which efficiently and economically form and deliver a sample plug to a separation channel and/or analytical device.

SUMMARY OF THE INVENTION

Apparatus and methods have been developed for rapid, automated analysis of microscale samples using pressure differentials. A sample plug formation device of the invention generally comprises two intersecting channels, an introduction channel and a separation channel. A sample is introduced through an opening in a first channel, referred to herein as a sample introduction channel. The sample moves through the sample introduction channel by vacuum, pressure, capillary action, or a combination thereof. At a distance from the point of sample introduction, the sample introduction channel forms a juncture or junction with (*i.e.*, intersects) a second channel, referred to herein as a separation channel. Through the use of pressure and/or vacuum applied to the separation channel and/or the sample introduction channel, a portion of the sample is transported into the separation channel as the bulk sample crosses the junction between the sample introduction and separation channels. With the proper control, a discrete plug of sample reproducibly may be formed in the separation channel and subjected to separation techniques and/or analysis. Subsequent to the formation of the sample plug, the portion of sample which does not form the sample plug typically is moved to a waste outlet.

Formation of the sample plug at the channel junction is controlled by application of pressure differentials in and between the sample introduction and separation channels. A first pressure differential is applied so as to induce sample flow through the introduction channel to the juncture. Subsequently, at least a second pressure differential is applied to move a portion of the sample into and along the axis of the separation channel. A plug of sample generally is formed in the separation channel at the junction when pressure is increased axially along the separation channel relative to the sample introduction channel. The frequency and size of plug formation is controlled by controlling the pressure differentials.

The sample introduction and separation channels may be capillaries formed to intersect at a junction. A preferred structure defining the sample introduction and separation channels is a microfabricated solid, such as a microchip. Typically, channels are etched directly into the microchip. In a preferred embodiment, the microchip comprises a series of sample introduction and separation channels etched onto its surface. Such channels preferably have cross-sectional dimensions of between about 0.1 μm and about 1000 μm .

- 4 -

In a preferred embodiment, the separation channel comprises a longitudinal axis containing a medium, e.g., water, an electrolyte, or a polyacrylamide solution or gel, which aids the separation of components suspected to be in the sample. Thus, a sample plug that is formed at the junction of the sample introduction and separation channels migrates axially along the separation channel where it may be separated into its components. Preferably, the sample introduction and separation channels contain a buffer that is compatible with the sample and separation medium, if present. The device may further comprise a voltage generator for applying a voltage axially along the longitudinal axis of the separation channel. The application of a voltage along the separation channel may aid in the separation of components of the sample, e.g., when the separation is accomplished by electrophoresis.

Also in a preferred embodiment, a device of the invention comprises a detector. The detector is placed in proximity to the separation channel for detecting separated components of a sample. The detector may include an ultraviolet detector, a visible light detector, an infrared detector, a fluorescence detector, a chemiluminescence detector, a refractive index detector, a Raman detector, a mass spectrometer, an electrochemical detector and/or a conductivity detector. Preferably, the detector is a mass spectrometer, a fluorescence detector, or radioactivity detector.

A sample plug formation device of the invention may be used in conjunction with a sample delivery system. A preferred sample delivery system is disclosed in co-owned, co-pending U.S. patent application, Serial No. 09/(to be amended in when available; identified by Attorney Docket No. SYP-131), entitled "Apparatus And Methods For Sample Delivery," which is incorporated by reference herein. In a preferred embodiment of the application, a chemical reaction takes place in a sample delivery system, and the products of the reaction are charged to a sample introduction channel of a device of the present invention.

A preferred sample delivery device has a housing defining a capillary which has an open end for introduction of a sample and a closed end. The closed end preferably is associated with a temperature control device which is used to control movement of sample and reactants into the sample delivery system. Immobilized within the capillary may be chemical reagents, such as, binding proteins, ligands, receptors, antibodies, or antigens. These reagents may be detectably labeled and, preferably, are fluorescently labeled. These reagents also may be chemically or enzymatically labelled, e.g., to permit amplification prior to detection.

- 5 -

The present invention provides for rapid, accurate, and reproducible analysis of microscale samples. When used in conjunction with a sample delivery device as described above, the analysis of a sample is an automated process from start to finish. Moreover, the automated process may include one or more reactions which may occur within the sample delivery device. The invention will be understood further upon consideration of the following drawings, description, and claims.

DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic diagram of a sample plug formation device of the invention. A sample introduction channel forms a non-parallel juncture with a separation channel in which a sample plug is formed. The direction of sample flow is shown by arrows 16, 18, and 20.

Figure 2: A-F are schematic cross-sectional views of a device of the invention showing flow of sample through the channels at various stages during the practice of a method of the invention.

Figure 3: A-F are schematic cross-sectional views of a device of the invention showing flow of sample through the channels with application of a "stacking" voltage along the separation channel.

Figure 4 shows a preferred embodiment of the invention which is a microchip assembly etched with a series of sample introduction channels and separation channels. The depicted microchip has connections which control the pressure and/or voltage through the channels.

Figure 5 shows a sample delivery system in association with a microchip assembly embodiment of the present invention as depicted in Figure 4. The sample delivery system includes an array of capillaries pre-loaded with a set of chemical reagents and in association with a temperature control device. The capillaries are positioned over the microchip assembly and are used to deliver sample to the sample introduction channels of the microchip assembly.

Figure 6 shows an array of capillaries containing a first set of chemical reagents and a second set of chemical reagents. A temperature control device is shown in association with the capillaries. A second temperature control device for localized heating and cooling also is shown. The capillaries are positioned over a microchip assembly for delivery of samples to the sample introduction channels.

- 6 -

Figure 7 depicts a scientific instrument of the invention which includes an integrated sample delivery system, sample plug formation device and other related equipment for performing rapid, automated analysis of microscale samples.

Like reference characters in the respective drawn figures indicate corresponding parts.

5 DETAILED DESCRIPTION OF THE INVENTION

The present invention provides for the automated formation of a sample plug which may be separated into its individual components and/or analyzed. As used herein, the term "sample" is intended to mean any source suspected to contain any component to be detected or identified, or any potentially reactive chemical entity. A sample can be "neat" or can be diluted with an appropriate solvent. Currently preferred samples include, but are not limited to, any biological specimen suspected to contain a component of interest. Samples suitable for use in the claimed invention include, but not limited to body fluids such as blood, serum, plasma, urine, cerebrospinal fluid, saliva, sweat, semen, tears, vaginal fluid, amniotic fluid, and ascites fluid.

As used herein, the term "component" is intended to mean any identifiable or detectable substance, or a substance susceptible to separation from other substances in a sample using an apparatus of the invention. Preferred components include, but are not limited to, chemical and biochemical moieties, such as proteins, peptides, nucleic acids, peptide hormones, non-peptide hormones, drugs of abuse, pharmaceuticals, microbial antigens, viral antigens, carbohydrates, polyclonal antibodies, monoclonal antibodies, anti-idiotypic antibodies, antibody fragments, enzyme substrates, enzyme inhibitors, biotin, receptors, ligands, inhibitors, and binding competitors. Components also may be bound to a probe, and in particular, a detectably-labeled probe. Common probes include polynucleotides, riboprobes and peptide nucleic acids (PNAs).

Broadly, the invention provides apparatus and methods for analysis of a microscale sample. However, any size sample may be analyzed with an appropriately sized sample analysis device of the invention using concepts and principles disclosed herein. An apparatus of the invention has a housing which defines two channels. The two channels intersect to form a junction. Sample is introduced into a first channel, the sample introduction channel. The sample introduction channel intersects a second channel, the separation channel. The channels may intersect at any angle to form the junction. The separation channel typically is longer than the length of the sample introduction channel. Preferably, the separation channel is greater than ten

- 7 -

times longer than the sample introduction channel and more preferably, greater than one hundred times longer. If the difference in lengths of the sample introduction channel and the separation channel is not extremely large, the cross section of the sample introduction channel may be larger to compensate for the pressure drop, i.e., to reduce the pressure drop.

5 An apparatus of the invention further comprises a pressure control device to apply pressure gradients to the channels. The pressure control device itself may be a positive pressure source such as a peristaltic pump, or a vacuum source such as a vacuum pump. A vacuum source also may be an absorbant device such as a wick which draws liquid into a channel using surface tension (capillary action). However, the pressure control device may include a controllable
10 pressure source, e.g., a vacuum source or a positive pressure source such as a peristaltic pump or a source of pressurized gas. Accordingly, the pressure control device may include hardware such as valves, manifolds, tubing and the like. The pressure control device also may include controllers such as any suitable microprocessor based programmable logic controller, personal computer controller, or the like for process control. A suitable controller includes features such
15 as programmability, reliability, flexibility, and durability. The suitable controller includes various input/output ports used to provide connections to open and close valves, regulate and meter fluids, among other features. The controller also includes sufficient memory to store process recipes for desired applications. Of course, the type of controller used depends upon the particular application.

20 Application of a pressure gradient within the channels moves sample through the channels. The channels preferably are formed on a microfabricated solid, such as, e.g., a microchip. The separation channel may have sieving media, such as polyacrylamide as a viscous solution or a gel, disposed therein to facilitate separation and/or analysis. After separation, the sample components may be detected using a detector disposed along or near the end of the
25 separation channel. The apparatus may be used to automatically perform assays such as, among others, immunoassays, enzyme assays, chemical assays, receptor assays and polynucleotide identifications.

 An apparatus of the invention provides for the automated, uniform preparation of a sample plug through the use of vacuum and/or positive pressure on the sample introduction and
30 separation channels. The sample introduction and separation channels define an injection system of a scientific instrument of the invention. As illustrated in Figure 1, the sample introduction

- 8 -

channel 10 forms a junction 11 with the separation channel 12. Alternately applying positive pressure and/or vacuum to the channels causes a sample plug 14 to form downstream of the junction in the separation channel 12. (It should be understood that Figure 1 is a schematic representation and that in practice, the sample plug 14 is contained within the channels.) Arrows 16, 18, and 20 show the direction of sample flow. Voltage generator 19 may be used to apply a voltage gradient along the longitudinal axis of the separation channel. For example, a voltage gradient may be applied while a pressure differential moves sample through the sample introduction channel in one type of sample plug formation process referred to as "stacking," more fully described below.

10 To assist in automating the methods described herein, another aspect of the invention is a scientific instrument which contains the sample analysis apparatus described above. The scientific instrument permits the efficient automation of the systems of the invention with its auxiliary devices and equipment. The scientific instrument also permits other apparatus, e.g., a sample delivery system, to be linked to the analysis systems of the invention to allow a functional design to suit the end users needs. For example, analytical instruments may be linked to a scientific instrument of the invention to permit analysis of samples, e.g., at given times in the reaction cycle. Analytical instruments useful in the invention will be well known to those skilled in the art and include, but are not limited to, mass spectrometry instruments, chromatography systems, and various detection instruments such as ultraviolet, infrared, fluorescent, and refractive indices detectors. Such a detector may be positioned away from the junction and in communication with the separation channel.

Other non-limiting examples of auxiliary instruments useful in the invention include diagnostic instruments for performing assays, and synthesizers for automating the production of particular compounds to become part of a sample. Such synthesizers include those capable of performing combinatorial syntheses which permit the screening of libraries of compounds with the delivery systems of the invention. All of the above instruments and devices may be operated manually in a step-wise fashion. However, full automation is preferred. As appreciated by a skilled artisan, automation preferably includes a microprocessor and/or computer which controls various aspects of the methods of the invention, but typically at least is in communication with the means for generating the pressure differentials.

- 9 -

Methods of the invention provide for the formation of a sample plug and, in certain embodiments, for separation of the components of that sample plug. The application of pressure/vacuum serves to push or pull the sample through the channels of the injection system of an apparatus of the invention. After a sample plug is formed in the separation channel, its components may be separated, preferably by electrophoresis. However, a metered sample plug may be transported to another analytical device for analysis without further separation. Figures 2A-2F illustrate the various stages of sample plug formation. Numerous means exist for introducing a sample into the apparatus, e.g., injection from a syringe or the like, or introduction from a sample delivery system known in the art. In another embodiment, an absorbent material, such as cotton, may be placed in the introduction channel. The absorbent material attracts sample into the sample introduction channel by capillary action. In another embodiment, an absorbent material may be placed in contact with the outlet of the sample introduction channel, e.g., above the channel, so that the absorbent material draws the sample through the sample introduction channel by creating a vacuum from surface tension (capillary action).

As shown in Figure 2A, sample 22 is deposited in the sample introduction channel 10. In Figure 2B, application of a first pressure differential, i.e., a vacuum, to the sample introduction channel opposite where the sample was introduced draws sample through the sample introduction channel and across the junction 11 formed with the separation channel 12. In Figure 2C, application of a second pressure differential, i.e., another vacuum, to the separation channel draws a portion of the sample into the separation channel.

Application of a pressure differential to the separation channel 12 for a specific interval reproducibly produces discrete sample plugs. In Figure 2D, application of positive pressure to the separation channel from the direction opposite of sample 22 flow causes a plug of sample 14 to form downstream of the junction 11 while the remaining sample is moved to waste or back to the introduction location. In certain embodiments, the positive pressure may continue to move the sample plug through the separation channel to effect separation similar to operation of a chromatography column.

In a preferred embodiment, the separation channel contains a sieving medium for separation of the sample components based on charge or size. The sieving medium may comprise, for example, polyacrylamide, agarose, polyethylene oxide, polyvinyl pyrrolidone, and methylcellulose. Other sieving media such as chromatography particles may be used depending

- 10 -

on the particular application. In Figure 2E, the components of the sample are moved electrophoretically along the separation channel and are separated by application of a voltage gradient along the longitudinal axis of the separation channel 12. Separation of the sample components is achieved by standard electrophoretic methods. Finally, subsequent to separation and/or analysis, Figure 2F depicts positive pressure being applied from both directions along the separation channel to force the sample remnants out of the channels to cleanse the system.

It should be understood that the different pressure differentials used to form a sample plug in the separation channel may be adapted for a particular application. That is, whether vacuum and/or positive pressure are used, and in what sequence, depends upon the analysis to be conducted. Moreover, the timing, strength and location of the pressure differentials are variables which should be optimized using the general principles and concepts disclosed herein. For example, in one embodiment, the first pressure differential applied to the introduction channel is reduced prior to the application of the second pressure differential to the separation channel. However, the specific examples discussed and depicted herein are meant to illustrate, but in no way limit, the present invention.

One way to manipulate the composition of a sample plug formed using methods of invention is to vary the ionic strength of the media, e.g., buffer solutions, in each channel. In the example depicted in Figures 2A-2F, the ionic strengths of the media in the sample introduction channel and the separation channel were substantially equivalent. As a result, the sample plug formed is not concentrated or diluted with respect to the ionic or charged species present in the sample. That is, concentration of the charged species in the sample plug should be approximately equal to their concentration in the initial sample charged into the sample introduction channel.

However, a sample plug also may be formed using a process called "stacking," which concentrates the charged components of a sample at the junction prior to sample plug formation. Basically, when an electric potential is applied axially along the separation channel while a pressure gradient moves a sample along the sample introduction channel, a region of increased ionic concentration results at the junction provided the medium in the sample introduction channel is at a lower ionic strength than the medium in the separation channel. This results in a sample plug which is more concentrated in one or more ionic species relative to the sample

- 11 -

introduced in the sample introduction. Modulation of the applied voltage permits a desired sample concentration to be realized.

Referring to Figures 3A-3F, the method of sample plug formation referred to as "stacking" is depicted using an apparatus of the invention. Figures 3A-3F show a series of diagrams similar to those in Figures 2A-2F, except that the ionic strength of the media in the sample introduction channel 10 is lower than the ionic strength of the medium in the separation channel 12. In addition, a voltage gradient is applied to the separation channel 12 while a vacuum moves sample along the sample introduction channel 10 as shown in Figure 3B. As understood by a skilled artisan, ionic species moving in an applied electric potential from a lower ionic strength medium to a higher ionic strength medium will experience a decrease in their rate of movement due to a decreased electric field in the higher ionic strength medium. Accordingly, as shown in Figure 3B, the ionic species "pile up" or concentrate at the interface 24 of the two differing ionic strength media. With the continuous flow of sample through the juncture, the ionic species in a sample may become highly concentrated at the interface 24. Subsequent to the appropriate amount of "stacking," the electric potential is removed and a pressure differential applied to the separation channel to form a sample plug which is concentrated in the ionic species of the sample as shown in Figures 3C and 3D. The remaining steps of the method, Figures 3E and 3F are as described above for Figures 2E and 2F.

The procedure of stacking may be useful to concentrate components in dilute samples so a detectable amount of the component or components of interest are transported through the separation channel. Alternatively, a sample medium may be diluted using "anti-stacking." Essentially the same procedure is practiced, however, the sample is in a higher ionic strength medium than is present in the separation channel. Accordingly, an optimized sample plug, e.g., its size and concentration of components, may be controlled by the above techniques, i.e., stacking, anti-stacking and non-stacking.

Figure 4 illustrates a preferred embodiment of the invention. A microchip assembly 25 etched with a series of sample introduction channels 10 and separation channels 12 is shown. The channels meet to form a junction 11. As depicted, the microchip has a plurality of sample introduction and separation channels. The channels are between about 10 μm and about 100 μm in width and about 0.1 μm to about 1000 μm in depth. The microchip also has manifolds 26 and

- 12 -

27 for transporting a sample and/or reagents to and/or within the separation and sample introduction channels.

Microchips having sample introduction and separation channels can be designed and fabricated in large quantities from a solid substrate material. They can be sterilized easily. Silica is a preferred substrate material because of the well-developed technology permitting its precise and efficient fabrication, but other materials may be used, including polymers such as polytetrafluoroethylenes. The sample introduction and separation channels may be fabricated inexpensively in large quantities from a silica substrate by any variety of micromachining methods known to those skilled in the art. The micromachining methods available include film deposition processes, such as spin coating and chemical vapor deposition, laser fabrication or photolithographic techniques, such as UV or X-ray processes, and etching methods, which may be performed by either wet chemical processes or plasma processes. (*See, e.g., Manz, et al., Trends in Analytical Chemistry* 10:144-149 (1991).)

Channels of varying widths and depths can be fabricated with microscale dimensions. A silicon substrate containing fabricated sample introduction and separation channels may be covered and sealed with a thin anodically bonded glass cover. Other clear or opaque cover materials may be used. However, to anodically bond properly, one of the substrate or cover should be silica and the other silicon. Accordingly, for example, a silica and a silicon substrate may be sandwiched, or a silicon substrate may be sandwiched between two glass covers. The use of a transparent cover results in a window which facilitates dynamic viewing of the channel contents and allows optical probing of the channels either visually or by machine. Other fabrication approaches may be used.

Samples to be analyzed may be delivered to the sample plug formation device of the invention by sample delivery systems, such as disclosed in co-owned, co-pending U.S. patent application, Serial No. 09/(to be amended in; identified as Attorney Docket No. SYP-131), entitled "Apparatus And Methods For Sample Delivery," which is incorporated by reference herein in its entirety. A preferred array of such sample delivery systems is shown in Figure 5. An array of capillaries 28 are held by an array holder 30. The inner diameter of the capillaries preferably is from about 5 μm to about 1000 μm , and more preferably from about 20 μm to about 300 μm . Although dimensions are provided for substantially circular cross sectional areas of

- 13 -

capillaries, similar cross sectional areas are preferred for non-circular channels, e.g., such as rectangular channels having a width and a depth.

One end of each of the capillaries is sealed and contacts a temperature control device 32. The capillaries also have an opening, which preferably is opposite the closed end. The capillaries may be made of, e.g., glass or plastic, and the temperature control device may be any commercially available or custom made heating and cooling device, e.g., a Peltier element. The capillaries further may contain chemical reagents 34 immobilized on their walls. Immobilization of the chemical reagents on the capillary walls may be accomplished by drying. The reagents may be delivered to the capillary by, e.g., injecting them into the capillary with a microneedle. Typically, the microneedle has a diameter smaller than the inside diameter of the capillary. Once the chemical reagents are in place, they may be dried by techniques known in the art. Alternatively, the reagents may be loaded hydraulically by heating and cooling to draw a solution containing the reagents into the capillary, drying the reagents at the desired location within the capillary, then washing those regions where reagents are not desired. The reagents also may be loaded by other techniques known in the art.

The chemical reagents immobilized in the capillaries may be binding proteins, ligands, receptors, antibodies or antigens for a component suspected to be contained in the sample. The reagents may additionally include buffers, surfactants, additives, excipients, carriers, haptans or other compatible molecules that facilitate or influence reaction with sample components.

The reagents also may comprise detectable moieties. As used herein, the term "detectable moiety" is intended to mean any moiety suitable for use in the claimed invention including, but not limited to: enzymes, fluorophores, biotin, chromophores, radioisotopes, colored particles, electrochemical or chemiluminescent moieties. A currently preferred detectable moiety is a fluorescent moiety, such as rhodamine. Other currently preferred detectable moieties include: fluorescein, cyanine dyes, coumarins, phycoerythrin, phycobiliproteins, dansyl chloride, and Texas Red.

A sample delivery system as described above may be positioned over the opening of a sample introduction channel of a microchip assembly 25 for delivery of a sample for analysis. In operation, the sample delivery systems pick up sample, allow the sample to react with the chemical reagents immobilized on their walls and then deliver the products of the reaction, if

- 14 -

any, to the sample introduction channels of a device of the invention. As shown in Figure 5, an array of such sample delivery systems simultaneously can deliver a plurality of samples to a plurality of sample introduction channels on a microchip assembly 25.

Modulation of temperature near the closed end of the capillaries by the temperature control device 32 controls the pick up and delivery of samples, i.e., the movement of sample within the capillaries. Since the capillaries are sealed at one end, heating and cooling the gas in the closed end of the capillaries causes that gas to expand or contract, respectively. When the gas is heated, the volume it occupies, and hence the pressure in the capillary, increases approximately according to the perfect gas law $PV=nRT$, where P is pressure, V is volume, n is the number of gas molecules, R is the constant $8.314 \text{ JK}^{-1}\text{mol}^{-1}$, and T is the temperature. Gas is therefore forced through the opening in the capillary when the gas is heated. The capillary then is submerged in the sample and cooled. Upon cooling, the gas in the capillary contracts and the sample enters the capillary. As the gas in the capillary contracts, the pressure in the capillary decreases. The pressure differential between the outside and inside of the capillary forces sample into the capillary.

Upon sufficient cooling, the sample contacts the chemical reagents immobilized on the capillary walls and reacts with those reagents. The time a sample is allowed to remain in contact with the reagents is determined by the reaction to be performed. Further heating and/or cooling of the capillary moves samples from a first location in the reactor to second and subsequent locations, where second or subsequent reactions take place. After the reaction is complete, reheating the capillary causes the gas to expand, forcing the sample from the capillary. If the capillary is positioned over the opening of a sample introduction channel of an apparatus of the invention, the sample is delivered directly to that apparatus for sample plug formation.

A sample delivery system used in conjunction with a sample analysis device of the invention may be used to conduct numerous types of chemical reactions. For example, the system and device may be used in diagnostic applications, such as blood testing (e.g., to identify blood components, or to detect/identify DNA in blood), immunoassays (e.g., to detect the presence of a specific antigen in a sample), or colorimetric or other assays (e.g. radiochemical, chemiluminescent, binding assays, and the like). The system and device may be used to detect toxins (e.g., bacteria, alcohol, drugs, viruses, organisms, metals, abnormal levels of physiological chemicals, and the like) or other components in a sample (e.g., a biological or environmental

- 15 -

sample). A sample delivery system also may be used in chemical synthesis (e.g., in the manufacture of drugs, peptides, nucleotides, *etc.*). In addition, a sample delivery system may be used in numerous laboratory techniques, such as peptide or nucleotide sequencing, amplification, or modification.

5 A sample delivery system which amplifies and aids in detecting target polynucleotide sequences also may be used to deliver sample to an apparatus of the invention. Figure 6 shows an array of capillaries 28 in thermal association with a temperature control device 32. Each capillary has one end sealed which is near the temperature control device 32. The capillaries each contain a first set of chemical reagents 38 and a second set of chemical reagents 40
10 immobilized on the capillary walls. A second temperature control device 42, which has conduits for warm and/or cool gas or liquid, permits control of the temperature in a discrete portion of the capillary, e.g., the region containing the chemical reagents. The sample delivery systems shown are positioned over a microchip assembly 25 for depositing the reaction products at the sample introduction channels 10 of an apparatus of the invention.

15 Use of the second temperature control device allows for the temperature of the reactions to be controlled without affecting the temperature of the gas in the closed end of the capillary. As described above in discussing Figure 5, heating the capillary causes the gas to expand and thus moves the sample within, or out of, the capillary. By heating a discrete portion of the capillary where the reagents and sample are located, the temperature of the reaction may be
20 controlled without moving the sample within the capillary. Various insulators present within or exterior to the capillary may be used to maintain a sample stationary within the capillary while also permitting localized heating and/or cooling. That is, the insulators can thermally shield the gas near the closed end of the capillary to prevent its expansion or contraction.

 In one embodiment of the invention, the first set of reagents 38 may be reagents for
25 performing a polynucleotide amplification reaction, such as PCR. PCR is well known in the art. See, e.g., U.S. Patent No. 5,330,892. In addition, other polynucleotide amplification reactions known in the art may be conducted using a reactor, including isothermal *in vitro* amplification of DNA using a restriction enzyme/DNA polymerase system, Walker, *et al.*, *Proc. Natl. Acad. Sci. U.S.A.*, 89: 392-96 (1992), and ligase chain reaction (LCR). Backman, *Clin. Chem.* 38: 457-58
30 (1992), each of which is incorporated by reference herein.

- 16 -

Reagents for performing PCR typically include a buffer, at least one primer, a polymerase, such as, e.g., *Taq* polymerase, and at least one nucleoside triphosphate. The choice of buffers, primers, and other components is within the skill in the art, depending upon characteristics of the sequence to be amplified (e.g., length, abundance in the sample, G/C content). A polymerase may be selected from the group consisting of *Taq* polymerase, E. coli DNA polymerase I, Klenow fragment of E. coli DNA polymerase I, T4 DNA polymerase, other available DNA polymerases, reverse transcriptase, and other enzymes, including heat-stable enzymes. The nucleoside triphosphates may include dCTP, dGTP, dATP or dTTP.

- The second set of reagents 40 includes probes for binding to amplified target DNA.
- 10 Probes for use in a reactor may be any DNA binding protein and may preferably be a complementary sequence, such as a riboprobe, a polynucleotide, or a PNA. It is preferable that the probes are detectably labeled. Preferred labels include radioisotopes, fluorescent or colorimetric labels, enzymatic labels, and molecular weight labels. A particularly preferred probe is a Peptide Nucleic Acid or PNA. Peptide nucleic acids are well-known DNA mimics with a neutral polyamide backbone on which the nucleic acid bases are attached in the same manner as they are attached to the phosphate backbone of DNA. See, Egholm, *et al.*, *Nature*, 365: 566-568 (1993); Oerum, *et al.*, *Nucl. Acids Res.*, 23: 5332-36 (1993); Pluskal, *et al.*, *The FASEB Journal*, Poster #35 (1994); *Practical PNA: Identifying Point Mutations by PNA Directed PCR Clamping*, PerSeptive Biosystems Vol. 1, Issue 1 (1995). Peptide nucleic acid synthons and oligomers are commercially available. (PerSeptive Biosystems, Inc., Framingham, MA). See, also, PCT publications EP 92/01219, EP 92/01220, and US 92 /10921, incorporated by reference herein. Peptide nucleic acid probes typically form more stable duplexes with DNA as compared to DNA/DNA duplexes. Additionally, because PNA/DNA complexes have a higher thermal melting point than the analogous DNA/DNA duplexes, use of PNA probes can improve the reproducibility of blotting assays.

- Fluorescein or biotin labeled PNA probes are synthesized on an Expedite Nucleic Acid Synthesis System (PerSeptive Biosystems). Spacer units of 8-amino-3,6-dioxaoctanoic acid (-o-) are added to resin-bound PNA before reacting activated esters of biotin (Bio) or fluorescein (Flu), such as dimethoxytritylbiotin ester of 1-(4'-nitrophenyl)pyrazolin-5-one (DMTr-bio-HPP) or 5,6-carboxyfluorescein-N-hydroxysuccinimide, with the PNA. After labeling, PNAs are cleaved from the resin and any protecting groups are removed using, for example, a

- 17 -

TFMSA/TFA/m-cresol/thioanisole (2:6:1:1) mixture for two hours at room temperature. Labeled PNA is precipitated by addition of anhydrous ether. Crude PNA precipitate is purified by high performance liquid chromatography on a Deltapack C18 column (Waters), and by Sephadex G-25 to remove fluorescent impurities.

5 Immobilization of the chemical reagents on the capillary walls may be accomplished by drying. The reagents may be delivered to the capillary by, for example, injecting them into the capillary with a microneedle. Other techniques for introduction of reagents into a capillary or channel have been discussed previously or would be known to skilled artisans. After the chemical reagents are in place, they are dried by, for example, blowing warm air over them or
10 placing them in an oven. The PCR reagents may be dried in a carbohydrate matrix, such as, for example, dextran or trehalose, prior to immobilization on the capillary walls. Each set of chemical reagents are preferably dried in separate rings around the capillary walls.

 In operation, the sample suspected of containing a target polynucleotide sequence is brought into contact with the first set of reagents in the capillaries (*i.e.*, the PCR reagents) by
15 heating the closed end of the capillary to expel gas, placing the capillary in the sample, and then cooling the closed end of the capillary to contract the gas and thus draw in the sample. Once the capillary is sufficiently cooled, the sample contacts the first set of chemical reagents. The second temperature control device 42, placed at a position on the reactor occupied by the PCR reagents, controls thermocycling. The second temperature control device 42 first increases temperature at
20 the position occupied by PCR reagents in order to denature double-stranded DNA in the sample. The same, or a different, temperature control device then cools the reactor region containing the PCR reagents to cause annealing of PCR primers to single-stranded template strands. Heating to a temperature intermediate between that for denaturation and that for annealing causes primer extension. A number of such cycles are repeated until the reaction is complete. The number of
25 PCR cycles, as well as the precise reagents used vary depending upon the amount of available template DNA, reaction efficiency, and other known factors. General protocols and parameters for PCR are known, and are available, for example, in *Short Protocols in Molecular Biology*, 15-1 - 15-40 (Ausebel, *et al.*, eds. 1995), incorporated by reference herein.

 Once PCR is complete, the amplified target sequence is brought into contact with the set
30 of complementary probes by cooling the gas in the closed end of the capillary with the temperature control device 32. The skilled artisan recognizes that a single temperature control

- 18 -

device may be used to heat or cool the capillary in order to move sample, and to heat or cool discrete capillary regions for PCR. However, as shown in Figure 6, separate temperature control devices are preferred. The set of probes may comprise multiple copies of a single probe that is known to hybridize with at least a portion of the amplified target, or the set may comprise a plurality of different probes, some hybridizing to portions of the target, some being non-complementary to the target.

The sample, comprising amplified nucleic acid, is brought into contact with the probes by cooling the capillary in order to cause sample to move up (away from the point of gas/sample entry) and into contact with the region of the capillary comprising probes, as referred to above.

10 Sample is allowed to incubate with the set of probes for a time sufficient to cause hybridization to a desired level of stringency. The hybridization parameters (*i.e.*, time, buffer, salt concentration, temperature, etc.) are determined based upon sequence length, G/C content, desired stringency, and other criteria known to the skilled artisan. *See, e.g.*, Ausubel, *supra* at 6-7. Once a desired level of hybridization has been achieved, sample (including hybrid duplex

15 formed between target and probe) is eluted into a sample plug formation device of the invention by further heating the reactor. Eluted sample may then be washed to remove excess (unbound) label. The target polynucleotide sequence is then detected using a sample analysis apparatus of the invention to determine the presence and/or amount of target DNA.

The sample analysis apparatus for injection, separation of sample components and

20 detection of labeled components may be combined with a sample delivery device as described above for the rapid, automated analysis of biological samples without the complex machinery, time and biohazard exposure inherent in existing systems. Figure 7 shows an integrated sample analysis apparatus and reactor array. The integrated device contains a sample card 44 having a membrane onto which a sample, such as, for example, blood is deposited. The card may be, *e.g.*,

25 an IsoCode™ card (Schleicher & Schuell, King, NH). The card may contain chemical reagents for lysing the cells of the sample deposited on the card membrane. The lysate then is dried by oven 46, thereby fixing the DNA from the lysed cells to the card membrane. The integrated device further comprises reactors 48, as described above with respect to Figure 5 or Figure 6. The device contains a microchip assembly 25 having sample introduction and separation

30 channels, which are connected to pressure/vacuum unit 50, high voltage power supply 52, and high pressure cartridge 54.

- 19 -

Near the end of the microchip assembly's separation channels is an optical detection module 56. The optical detection module detects the presence of detectable moieties bound to the component of interest in the sample. Detection can be achieved by methodologies including, but not limited to: absorbance of ultraviolet radiation, absorbance of visible radiation, fluorescence, refractive index, Raman or mass spectrometry, electrochemistry, and conductivity. Detection by fluorescence is preferred. Fluorescence detection using this module involves a microchip laser beam, which scans across the channels of the microchip.

The integrated device further comprises a sterile deionized water unit 58, a sieving gel buffer unit 60, and a micro-channel reconditioning solution unit 62. Each of these three units as depicted is divided into two halves with one half containing the fresh solutions and the other half containing waste solutions.

In operation, a sample is deposited onto the membrane of the sample card 44, and the card is inserted into the integrated device, as shown in Figure 7. The cells in the sample are lysed by the chemical reagents contained in the membrane. The cellular DNA, or other sample components, are then dried onto the membrane by heating with oven 46. At this point the card can be removed and archived, or it can be used in continued processing. Alternatively, a Guthrie paper dried blood blot may be used to deposit the sample.

After drying of the sample to the card, the card membranes are steam heated using sterile deionized water from unit 58 so as to extract the sample components into a small quantity of liquid. The capillaries of the reactors 48 are then heated to expel gas, moved into position over the membranes, and dipped into the liquid containing the sample. Upon cooling of the capillaries, the gas in the closed end of the capillaries contracts and sample is drawn into the capillaries. The capillaries are preferably pre-loaded with the reagents specific for the immunoassay or polynucleotide detection to be performed, as described above.

The sample once reacted in the capillaries, as described above, is deposited in the sample introduction channels of the microchip assembly 25. The capillaries move over so that they are positioned above the sample introduction channels. The capillaries are then heated by temperature control device 32 so that gas inside the closed end of the capillary expands and forces sample out of the capillary, as described above with respect to Figure 5 and Figure 6.

- 20 -

Once used, the sample delivery systems can be disposed of and new systems containing reagents for the next reaction of interest can be inserted into the integrated device.

Once deposited at the sample introduction channel of the microchip assembly, pressure/vacuum unit 50 is used to create a pressure gradient inside the sample introduction and separation channels of the microchip, and thereby inject the sample into the separation channel, as described above with respect to Figure 2. Voltage generator 52 may also be used to apply a voltage gradient to the separation channel to perform the stacking technique as described above with respect to Figure 3.

After formation of the sample plug in the separation channel, voltage generator 52 is used to apply a voltage axially along the separation channel of the microchip so as to separate the components of the sample. A sieving medium is pre-loaded into the channels of the microchip. The buffer from unit 60 is injected into the separation channels prior to formation of the sample plug.

As the samples reach the end of the separation channel, optical detection module 56 is used to detect the presence of the detectable moieties attached to the sample components within the separation channels. For polynucleotide identifications, the results of the optical detection are compared against data produced from genotyping experiments. This data is in the form of intensity vs. time graphs that are electronically searchable in determining matching similarity.

After performance of the analysis pressure from high pressure cartridge 54 is used to apply pressure at both ends of the separation channel so as to cleanse the channels of the microchip assembly. The channels are then reconditioned using reconditioning solution from unit 62. The microchip assembly can then be reused in subsequent analyses. Alternatively, the microchip assembly may be disposed of.

Compared to methods known in the art, a sample plug formation device of the invention uses pressure differentials to form a sample plug for separation and/or analysis. Advantages of the present invention include the ability to form and separate a sample plug containing non-ionic species, and the ability to form a sample plug without application of an electric field so that the surface characteristics of and the medium in the channel do not affect greatly sample plug formation. Accordingly, the present invention offers several advantages over plug formation devices and methods known in the art.

- 21 -

Additionally, when used in conjunction with a sample delivery system described above, further advantages are realized. Compared to the use of conventional volume controllers such as syringes and pumps, a thermally-controlled sample delivery system has fewer moving parts which may wear out or require extensive maintenance. Moreover, since the sample delivery system may be independent of an analytical instrument, other benefits are realized. For example, the sample delivery channels can be made of low cost materials such as plastic capillary tubing since optical quality or integrated electrodes are not required. Accordingly, single use of a channel is attractive which can eliminate a cleaning step and/or cross-contamination.

In addition, since the channels typically are not used directly in an analytical technique, the channels may be readily moveable and have a higher degree of tolerance for positioning with a sample plug formation device of this invention. That is, since the detection system of an analytical device typically remains stationary, the optical alignment of a liquid detection capillary needs to be done once for optimal accuracy during the analysis of a plurality of samples. Furthermore, if the sample delivery system contains a chemical reagent and is used to perform a reaction, any particulates present or formed during the reaction easily can be filtered prior to introduction of the reaction products to a sample plug formation device thereby preventing clogging and/or inaccurate analysis. These above features permit simple and inexpensive automation robotics to be used.

Compared to using traditional systems which rely on capillary action to deliver, mix and/or react chemicals, a sample delivery system of the invention exhibits several advantages. The surface of a channel of a sample delivery system of the invention may be hydrophilic or hydrophobic in contrast to a capillary action surface which requires a hydrophilic surface. Also with respect to the surface of the channel, the reproducibility of sample solution metering is less dependent of the surface characteristics and sample constituents. In addition, the sample delivery system of the invention allows direct control over the metering of samples and reagents, and permits bubble segregation to be practiced routinely. These benefits not only are achieved by the sample delivery system described above, but also with respect to a sample plug formation device of the invention which uses pressure differentials.

Compared to electro-osmotic flow for delivering, mixing and/or reacting chemicals, a sample delivery system which uses pressure exhibits some of the same advantages compared to using capillary action discussed above, i.e., surface characteristics and reproducibility of solution metering. Moreover, the sample delivery system typically is unrestricted in its solution

- 22 -

composition for conducting analysis and/or chemical reactions. That is, variables such as pH, ionic strength, buffer composition, chemical additives and solvents often are unlimited depending upon the particular application. These variables typically are restricted for effective electro-osmotic flow to occur. Again, as mentioned above, these benefits not only are realized
5 with the sample delivery system described above, but also with respect to a sample plug formation device of the invention which uses pressure differentials.

Therefore, as described and illustrated above, the present invention allows for high speed analysis of microscale biological samples without the complexity, time, labor and biohazard exposure of conventional techniques. Additional aspects and embodiments of the invention are
10 apparent upon consideration of the foregoing disclosure. Accordingly, the scope of the invention is limited only by the scope of the appended claims.

The invention may be embodied in other specific forms.

- 23 -

What is claimed is:

- 1 1. A sample plug formation device comprising:
2 a housing defining
3 a separation channel comprising a longitudinal axis, and
4 an introduction channel which forms a juncture with the separation
5 channel; and
6 a pressure control device independently in communication with the separation
7 channel and the introduction channel wherein
8 a first pressure differential applied to the introduction channel transports a
9 sample to the juncture, and
10 a second pressure differential applied to the separation channel transports a
11 portion of the sample in the juncture into the separation channel to form a sample plug.
1 2. The sample plug formation device of claim 1 further comprising a separation
2 medium disposed within the separation channel.
1 3. The sample plug formation device of claim 1 wherein the housing comprises a
2 microfabricated solid.
1 4. The sample plug formation device of claim 1 wherein the introduction channel
2 and the separation channel independently have a mean diameter within the range of about 0.1 μm
3 to about 1000 μm .
1 5. The sample plug formation device of claim 1 further comprising a voltage
2 generator in communication with the separation channel to apply an electric potential along the
3 longitudinal axis.
1 6. The sample plug formation device of claim 1 wherein the pressure control device
2 comprises a controllable pressure source.
1 7. A scientific instrument comprising the sample plug formation device of claim 1.
1 8. The scientific instrument of claim 7 further comprising a computer in
2 communication with the pressure control device to control the pressure control device.
1 9. The scientific instrument of claim 7 further comprising a detector spaced apart
2 from the junction and in communication with the separation channel to detect a chemical
3 component.
1 10. The scientific instrument of claim 7 further comprising a thermally controlled
2 delivery system to introduce the sample into the introduction channel.
1 11. A method for forming a sample plug comprising the steps of:

- 24 -

- 2 (a) providing a sample plug formation device comprising:
3 a housing defining
4 a separation channel comprising a longitudinal axis, and
5 an introduction channel which forms a juncture with the separation
6 channel; and
7 a pressure control device in communication with the separation channel;
8 (b) applying a first pressure differential to the introduction channel to
9 transport a sample in communication with the introduction channel to the juncture; and
10 (c) applying a second pressure differential to the separation channel to
11 transport a portion of the sample in the junction into the separation channel to form a sample
12 plug.

1 12. The method of claim 11 wherein the first pressure differential applied to the
2 introduction channel is reduced prior to the application of the second pressure differential to the
3 separation channel.

1 13. The method of claim 11 further comprising the step of applying an electric
2 potential along the longitudinal axis.

1 14. The method of claim 13 wherein applying an electric potential along the
2 longitudinal axis occurs during step (b).

1 15. The method of claim 13 wherein applying an electric potential along the
2 longitudinal axis separates components in the sample plug.

1 16. The method of claim 14 further comprising the step of analyzing for a component
2 in the sample plug.

1 17. The method of claim 11 further comprising the step of applying positive pressure
2 to the separation channel to move the sample plug along the separation channel.

1 18. The method of claim 17 wherein applying positive pressure separates components
2 in the sample plug.

1 19. The method of claim 18 further comprising the step of analyzing for a component
2 in the sample plug.

1 20. The method of claim 11 wherein applying the second pressure differential to the
2 separation channel is for a specified interval.

1 21. The method of claim 11 further comprising the step of providing a thermally
2 controlled sample delivery device to communicate the sample with the introduction channel.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C



FIG. 2D




FIG. 2E





FIG. 2F

3/7



4/7




FIG. 4

SUBSTITUTE SHEET (RULE 26)

5/7




FIG. 5




FIG. 6




FIG. 7

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
26 October 2000 (26.10.2000)

PCT

(10) International Publication Number
WO 00/63704 A3

- (51) International Patent Classification⁷: G01N 27/447, B01L 3/00
Lance; 45 Washington Street #86, Methuen, MA 01844 (US).
- (21) International Application Number: PCT/US00/08930
(74) Agent: BRODOWSKI, Michael, H.; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).
- (22) International Filing Date: 4 April 2000 (04.04.2000)
- (25) Filing Language: English
(81) Designated State (national): JP.
- (26) Publication Language: English
(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- (30) Priority Data: 09/293,313 16 April 1999 (16.04.1999) US
Published:
— With international search report.
- (71) Applicant: PERSEPTIVE BIOSYSTEMS, INC.
[US/US]; 500 Old Connecticut Path, Framingham, MA 01701 (US).
(88) Date of publication of the international search report:
8 February 2001
- (72) Inventors: TAYLOR, Todd, A.; 10 Vernon Street, Framingham, MA 01701 (US). CARSON, William, W.; 14 Schofield Road, Hopkinton, MA 01748 (US). KOUTNY, *For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: APPARATUS AND METHODS FOR SAMPLE ANALYSIS



(57) Abstract: The present invention is directed to apparatus and methods for rapid, automated, microscale sample analysis using pressure differentials. The invention includes an apparatus having intersecting channels for introduction of a sample and separation of that sample into its components. The sample introduction and separation channels preferably are etched in a microfabricated device, such as a microchip, to form a junction. Pressure gradients are applied to the channels to form a sample plug in the separation channel. The separation channel may have disposed within it a medium for separation of the components suspected to be contained in the sample. For example, with the proper medium, a voltage gradient may be applied along the separation channel to separate the components of the sample electrophoretically. The apparatus also may include means for detecting the components of the sample subsequent to separation.

WO 00/63704 A3

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 00/08930

A. CLASSIFICATION OF SUBJECT MATTER
G01N27/447,B01L3/00

According to International Patent Classification (IPC) or to both national classification and IPC¹

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
G01N,B01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5779868 A (PARCE et al.) 14 July 1998.	1, 11
A	EP 0608120 A2 (HEWLETT-PACKARD COMPANY) 27 July 1994.	1, 11
A	US 4315754 A (RUZICKA et al.) 16 February 1982.	1, 11

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search
19 July 2000

Date of mailing of the international search report
19. 10. 00

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer
NARDAI

ANHANG

Zum internationalen Recherchenbericht über die internationale Patentanmeldung Nr.

In diesem Anhang sind die Mitglieder der Patentfamilien der im obengenannten internationalen Recherchenbericht angeführten Patentdokumente angegeben. Diese Angaben dienen nur zur Unterrichtung und erfolgen ohne Gewähr.

ANNEX

To the International Search Report to the international Patent Application No.

PCT/US 00/08930 SAE 278322

This annex lists the patent family members relating to the patent documents cited in the above-mentioned search report. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

ANNEXE

Au rapport de recherche international relatif à la demande de brevet international n°

La présente annexe indique les membres de la famille de brevets relatifs aux documents de brevets cités dans le rapport de recherche international visée ci-dessus. Les renseignements fournis sont donnés à titre indicatif et n'engagent pas la responsabilité de l'Office.

Im Recherchenbericht angeführte Patentdokumente Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
US A 5779868	14-07-1998	AU A1 35012/97	21-01-1998
		BR A 9710052	11-01-2000
		CA AA 2258481	08-01-1998
		CN A 1228841	15-09-1999
		EP A2 815940	07-01-1998
		EP A3 815940	01-04-1998
		EP A1 909385	21-04-1999
		US A 5880071	09-03-1999
		US A 5958203	28-09-1999
		US A 5972187	26-10-1999
		US A 6042709	28-03-2000
		US A 6080295	27-06-2000
		WO A1 9800705	08-01-1998
EP A2 608120	27-07-1994	JP A2 6242073	02-09-1994
EP A3 608120	19-04-1995	US A 5482608	09-01-1996
US A 4315754	16-02-1982	DE A1 3031417	11-06-1981
		DE C2 3031417	15-02-1996
		FR A1 2469714	22-05-1981
		FR B1 2469714	21-06-1985
		GB A1 2062225	20-05-1981
		GB B2 2062225	13-06-1984
		JP A2 56036053	09-04-1981
		JP B4 2056637	30-11-1990

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.